

OUTBREAK™

POWER OVER ETHERNET SPLITTER



POE splitter for delivering power via POE to non-POE network devices

Delivers 5V or 12V DC to non-POE devices from a POE network source by splitting data and power.

Simple POE splitter delivering clean power to non-POE devices

Fully IEEE 802.3af compliant and gigabit compatible

Steps down POE voltage (48V) to 5V or 12V DC

Compact unit with integral wall mount lugs

Ideal for non-POE wireless access points, IP phones, IP cameras

TECHNICAL SPECIFICATION] OUTBREAK™

POWER				
Input voltage	36V to 56V DC, receiving power on either data or spare pairs			
Input current	0.6A at 36V maximum load			
OUTPUT POWER				
OUTBREAK 5	12.5 watts at 5V DC			
OUTBREAK 12	12-14 watts at 12V DC			
	Output with short-circuit protection			
DC Output connector	Barrel connector 9mm x 2.5mm x 5.5mm, centre positive			
POE STANDARDS				
	IEEE 802.3af POE			
ETHERNET INTERFACE				
	RJ45 Data and POE IN port			
	RJ45 Data OUT port			
	10/100/1000 Base-T compatible			
LEDS				
Status indicator	Green LED ON - Output OK			
PHYSICAL/ENVIRONMENTAL				
Dimensions	L 100mm (excluding flying lead) W 56mm H 28mm			
Weight	200g [7.0oz]			
Mounting	Integral wall-mount lugs			
Operating temperature	0°C to +40°C [32°F to 104°F]			
Relative humidity	5% to 90% non-condensing			
Compliance	CE, FCC, RoHS			
PRODUCT CODES		VOR-OB5	OUTBREAK 5V	5V POE Splitter
		VOR-OB12	OUTBREAK 12V	12V POE Splitter



Americas & Asia Sales :
Veracity USA Inc.
65 Harristown Road
Glen Rock
NJ 07452

USA
Tel: 1-800-679-1590
Fax: 1-800-679-0714
www.veracityglobal.com
sales@veracityusa.com

EMEA Sales :
Veracity UK Ltd
Prestwick International Aerospace Park
4 Dow Road
Prestwick
KA9 2TU
UK
Tel +44 (0) 1292 264967
Fax +44 (0) 845 528 1081
www.veracityglobal.com
sales@veracityuk.com