UniFi® Network USW Lite 8 PoE

Datasheet
USW-Lite-8-PoE

UniFi® | SWITCH



UniFi Switch Lite 8 PoE

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices.
Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.



Mechanical

Dimensions	99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25")
Weight	450 g (15.87 oz)

Hardware

Total Non-Blocking Line Rate	8 Gbps
Max. Power Consumption	8W
Power Method	54VDC, 1.1A Power Adapter
Power Supply	External 54V/60W Power Adapter
Supported Voltage Range	DC 50V to 57V
Networking Interfaces	(8) 10/100/1000 Mbps Ethernet RJ45 Ports
PoE Interfaces	(4) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Mangement Interface	Ethernet In-Band
Max. PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifcations	CE, FCC, IC

LEDs

System	(1) Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at

Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: www.ui.com/support/warranty
©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, and UniFi are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.