RG-EST310 V2

5GHz Dual-stream 802.11ac 1KM Wireless Bridge

DATASHEET

Highlights

- RG-EST310 V2 provide stable traffic transmission from 1KM away.
- Automatic pairing and automatic healing
- IP54 Weatherproof, -30℃~55℃ ensures stable operating
- Cost-effective wireless solution for elevator CCTV to avoid cable loss

Highlight Features

Highlight Features

Strong Adaptability and High Scalability

V0 Level
Flame Retardant

IP54
Weatherproof

-30 to 55 ℃ Operating
Temperature

High Quality
High Performance

RG-EST310 V2 has adopted the new high-performance 5GHz single-band dual-stream chip solution, which offers up to 867Mbps wireless transmit rate and significantly enhances the efficiency and stability of network bridge data transmission.

Highlight Features

Specifications

Basic	
Radio Design	5 GHz Single-Band Dual-Stream
Transmission Protocol	IEEE 802.11 ac/n/a
Operating Band	802.11a/n/ac: 5.150~5 .350GHz, 5.470~5.725GHz , 5.725~5 .850GHz (country specific)
Antenna	Directional antennas, 10 dBi
Polarization	Horizontal: 60°, Vertical: 30°
Bridging Distance	1 KM (recommended)
Spatial Streams	2x2, MU-MIMO
Memory/Flash	64 MB/8 MB
Maximum Throughput	Up to 867 Mbps at 5 GHz
Ports	1 10/100Base-T Ethernet ports, port 1 with Passive PoE
Max. Transmit Power	≤400 mW(26 dBm) (adjustable)
IP Rating	IP54
Lightning Protection	4 KV
Installation	Wall-mounted/ Pole-mounted
Weight	0.35 kg
Dimensions (D x W x H)	147 mm × 76 mm × 37 mm

Software Features	
IPv4	
802.1Q VLAN	✓
Multi-VLAN Transparent Transmission	✓
ARP	256
Max. Concurrent Connections	8000
Ping	✓

Specifications

Software Features	
IPv4	
Traceroute	✓
Unicast traffic	✓
DHCP Client	✓
DNS Client	✓
Static IP address	✓
IP Collision Avoidance	✓
Management IP	192.168.120.1
Routing	
Default Route	✓
Wireless	
SSID/SSID Hiding	✓
Password	Open / WPA-PSK / WPA2-PSK / WPA/WPA2-PSK
RSSI	-52/100M -65/500M -68/1KM -75/2KM
Performance	90Mbps/100M(HT40) 80Mbps/500M(HT40) 80Mbps/1KM(HT40) 40Mbps/2KM(HT40)
One-Click Optimization	✓
DFS	✓
Local Forwarding	✓
WLAN QoS	WMM
Management	
Zero Provisioning on Cloud	QR-Code / Serial Number
CWMP(TR069) Support	✓

Specifications

Software Features	
Management	
Point-to-Point	✓
Point-to-Multipoint	Recommended 5
Self-Organizing Network	Max. 200 wireless bridges
AP/CPE Switchover	✓
Interface Configuration	✓
Country Code	176 countries support, details refer to Country&Region Code reference
Clock setting	✓
Time Zone	✓
Maintanance	
Alarm	IP address conflict / SSID / Offline
Diagnostics	✓
Reboot	✓
Reset	✓
Cloud Features	
Remote Access	✓
Remote Reboot	✓
Statistics Monitoring	✓
Working mode	Normal / High performance / Anti-interference
Remote SSH	✓
Remote EWeb	✓
Camera Reference	
3Mbps Video Bit Rate	16 Units/100M 16 Units/500M 16 Units/1KM 6 Units/2KM

Specifications

Software Features	
Camera Reference	
4-5Mbps Video Bit Rate	10 Units/100M 10 Units/500M 10 Units/1KM 4 Units/2KM
6Mbps Video Bit Rate	7 Units/100M 7 Units/500M 7 Units/1KM 3 Units/2KM

Hardware Features	
Physical Features	
LED indicator	LEDs indicate the bridging quality: LED off: No bridging LED blinking: ≤-78dBm One LED on: -78dBm< RSSI ≤-72dBm Two LEDs on: -72dBm< RSSI ≤-65dBm Three LEDs on: >-65dBm
Hardware Button	1 reset button
Power Supply	12 VDC power supply or 24 VDC Passive PoE
Power Consumption	< 7W
Environment	Operating temperature: -30°C to 55°C (-22°F ~ 131°F) Storage temperature: -40°C to 70°C (-40°F ~ 158°F) Operating humidity: 5% to 95% (noncondensing) Storage humidity: 5% to 95% (noncondensing)
MTBF	> 400,000H

Package Contents

Device	**RG-EST310 V2 * 2**
Mounting Bracket	**2**
Hose Clamps	**4**
Power supply	**Power adapter * 2**
User Manual	**1**
Wall Anchors	**4**
Phillips Pan Head Screws	**8**
Package Weight	**1.35 kg**
Package Dimension (w x d x h)	**400*231*88mm**

Redefine your easy network

Copyright ©2000-2023 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.

Ruijie Networks Co., Ltd.
Building 19, Juyuanzhou Industrial Park, No.618
Jinshan Road, Cangshan District, Fuzhou, Fujian, China
Website: https://www.ruijienetworks.com