

BDCOM S1200 Series POE Switches

BDCOM S1200 Series POE Switches

Product Overview

BDCOM S1200 POE Series is a large-power POE switch of 100M access to 1000M in the uplink designed for the video surveillance network and WiFi access network in the medium and small POE networks. BDCOM S1200 POE Series has three models: S1210-8P-150, S1210-16P-330 and S1226-24P-330, which meets the need of networks of different scales.



- 8 100M POE ports +1 gigabit Base-T port+1 gigabit SFP port
- Switching Capacity: 5.6Gpbs
- Dimensions (W×D×H)(mm):160*92.5*28

S1210-8P-150



- 16100M POE ports +2 gigabit combo ports
- Switching Capacity: 7.2Gpbs
- Dimensions (W×D×H)(mm): 440*232*45

S1218-16P-330



- 24 100M POE ports +2 gigabit combo ports
- Switching Capacity: 8.8Gpbs
- Dimensions (W×D×H)(mm): 440*232*45

S1226-24P-330

Product Characteristics

Switching Characteristics

- Non-block switching architecture and wire-speed forwarding supported by all ports;
- Integrated professional thunder-proof electric circuit, which is adaptable to the outdoor environment;
- Large buffer memory with no video interruption;
- IEEE802.3x full duplex flow control and Backpressure half-duplex flow control;
- Operating status monitoring and fault analysis through indicators on the panel.

Practicability



- Plug and play; no need of configuration;
- Easy and secure device maintenance;
- Easy and convenient installation

Flexible Networking Capacity

BDCOM S1200 POE Series supports 8 10M/100M, 16 10M/100M Base-T ports or 24 10M/100M Base-T ports, which can meet the access requirement of different network scales. Besides, S1210-8P-150 provides with 1 uplink gigabit SFP port and 1 uplink gigabit Base-T port; S1218-16P-330 and S1226-24P-330 provides with two uplink combo ports, which can be flexibly connected to the core network, greatly expanding the range of application and saving the cost.

Product Specifications

Item	S1210-8P-150	S1218-16P-330	S1226-24P-330
Switching capacity	5.6G	7.2G	8.8G
MAC capacity	4K	4K	4K
POE power supply	8-port802.3af/at	16-port 802.3af/at	24-port 802.3af/at
Power supply	AC:100~220V，50Hz±10%		

Environment	Operating temperature/humidity: 0℃-40℃, 10%-90% non-condensing Storage temperature/humidity: -40℃-70℃； 5%-95% non-condensing
Heat dissipation	support
Thunder proof	6KV

Ordering Information

S1200 Series POE Switches	
S1210-8P-150	8-port 100M POE switch (8 100M POE Base-T ports, 1 gigabit Base-T port, 1 gigabit SFP port; standard AC220V power supply; 150W POE power, the cooling fan, desktop installation)
S1218-16P-330	16-port 100M POE switch (16 100M POE Base-T ports, 2 gigabit uplink combo ports; standard AC220V power supply; 330W POE power; the cooling fan, rack-mounted installation)
S1226-24P-330	24-port 100M POE switch (24 100M POE Base-T ports, 2 gigabit uplink combo ports; standard AC220V power supply; 330W POE power; the cooling fan, rack-mounted installation)

For More Information

For more information about the BDCOM S1200 Series, please contact your local BDCOM account representative.

Shanghai Baud Data Communication Co., LTD.
No.123, Juli Road,
Pudong Zhangjiang High-Tech Park,
Shanghai 201203, P.R.China
www.bdcom.cn
Tel: +86-21-50800666

Copyright ©Shanghai Baud Data Communication Co., LTD. 2017. All Rights Reserved.
This document is BDCOM Public Information.

BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time without notice.

