


## 8MP HD Wide Angle Intelligent IR Fixed Eyeball Network Camera IPC3608SB-ADF16KM-IO



## Features

- High quality image with 8 MP, 1/2.7" CMOS sensor
- 8 MP (3840 × 2160)@30/25 fps; 5 MP (3072 × 1728)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Wide angle technology realizes the horizontal viewing angle of 180°
- The dewarp level can be configured in the range of 1 to 9
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection
- Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles
- 120 dB true WDR technology enables clear image in strong light scene
- Built-in mic
- Smart IR, up to 20 m (65.6 ft.) IR distance
- MicroSD, up to 512 GB
- IP67 protection
- IK10 vandal resistant


## Specifications

| Model                      | IPC3608SB-ADF16KM-IO                                                                                                                |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Camera                     |                                                                                                                                     |
| Max Resolution             | 8 MP                                                                                                                                |
| Sensor                     | 1/2.7" CMOS                                                                                                                         |
| Min. Illumination          | Color: 0.01 Lux (F2.0, AGC ON), 0 Lux with IR on                                                                                    |
| Day/Night                  | IR-cut filter with auto switch (ICR)                                                                                                |
| Shutter                    | Auto/Manual, 1 ~ 1/100000s                                                                                                          |
| Adjustment Angle           | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°                                                                                |
| WDR                        | 120 dB                                                                                                                              |
| S/N                        | >52 dB                                                                                                                              |
| Lens                       |                                                                                                                                     |
| Focal Length               | 1.68 mm                                                                                                                             |
| Iris                       | F2.0                                                                                                                                |
| Field of View (H)          | 180°                                                                                                                                |
| Field of View (V)          | 100°                                                                                                                                |
| Field of View (D)          | 180°                                                                                                                                |
| Lens Type                  | Fixed                                                                                                                               |
| Iris Type                  | Fixed                                                                                                                               |
| DORI                       |                                                                                                                                     |
| DORI Distance (Lens)       | 1.68 mm                                                                                                                             |
| DORI Distance (Detect)     | 37.8 m (124.0 ft.)                                                                                                                  |
| DORI Distance (Observe)    | 15.1 m (49.6 ft.)                                                                                                                   |
| DORI Distance (Recognize)  | 7.6 m (24.9 ft.)                                                                                                                    |
| DORI Distance (Identify)   | 3.8 m (12.5 ft.)                                                                                                                    |
| Illuminator                |                                                                                                                                     |
| Illumination Distance (IR) | 20 m (65.6 ft.)                                                                                                                     |
| Wavelength                 | 850 nm                                                                                                                              |
| IR On/Off Control          | Auto/Manual                                                                                                                         |
| Supplemental Light         | IR                                                                                                                                  |
| Video                      |                                                                                                                                     |
| Video Compression          | Ultra 265, H.265, H.264, MJPEG                                                                                                      |
| H.264 Code Profile         | Baseline profile, Main profile, High profile                                                                                        |
| Video Bit Rate             | 128 Kbps to 16 Mbps                                                                                                                 |
| U-code                     | Support                                                                                                                             |
| OSD                        | Up to 8 OSDs                                                                                                                        |
| Privacy Mask               | Up to 4 areas                                                                                                                       |
| ROI                        | Support                                                                                                                             |
| Video Stream               | Triple streams                                                                                                                      |
| Frame Rate-Main Stream     | 8 MP (3840 × 2160), max. 30 fps; 5 MP (3072 × 1728), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 1080P (1920 × 1080), max. 30 fps |
| Frame Rate-Sub Stream      | 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 ×                                    |

|                                  |                                                                                                                                                                                                            |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                  | 288), max. 30 fps; CIF (352 × 288), max. 30 fps;                                                                                                                                                           |
| Frame Rate-Third Stream          | D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps                                                                                           |
| <b>Image</b>                     |                                                                                                                                                                                                            |
| Auto Scene Match (ASM)           | Support (only WDR)                                                                                                                                                                                         |
| White Balance                    | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                                       |
| Smart IR                         | Support                                                                                                                                                                                                    |
| Digital Noise Reduction          | 2D/3D DNR                                                                                                                                                                                                  |
| Flip                             | Normal, Flip vertical, Flip horizontal, 180°                                                                                                                                                               |
| Dewarping                        | Support                                                                                                                                                                                                    |
| HLC                              | Support                                                                                                                                                                                                    |
| BLC                              | Support                                                                                                                                                                                                    |
| Image Stabilization              | N/A                                                                                                                                                                                                        |
| Low Illumination Characteristics | Low-light                                                                                                                                                                                                  |
| Defog                            | Digital defog                                                                                                                                                                                              |
| <b>Intelligent</b>               |                                                                                                                                                                                                            |
| Smart Intrusion Prevention       | Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle)                       |
| Attribute Collection             | SIP with color retrieval                                                                                                                                                                                   |
| <b>Events</b>                    |                                                                                                                                                                                                            |
| Basic Detection                  | Motion detection, Ultra motion detection, Tampering alarm, Audio detection, Object removed, Object Left Behind                                                                                             |
| General Function                 | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| <b>Audio</b>                     |                                                                                                                                                                                                            |
| Audio Compression                | G.711U, G.711A, AAC-LC                                                                                                                                                                                     |
| Audio Bitrate                    | G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps                                                                                                                                                                   |
| Two-way Audio                    | N/A                                                                                                                                                                                                        |
| Suppression                      | Support                                                                                                                                                                                                    |
| Sampling Rate                    | G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz                                                                                                                                                        |
| <b>Storage</b>                   |                                                                                                                                                                                                            |
| Edge Storage                     | MicroSD, up to 512 GB                                                                                                                                                                                      |
| Network Storage                  | ANR, NAS (NFS)                                                                                                                                                                                             |
| <b>Network</b>                   |                                                                                                                                                                                                            |
| Protocols                        | IPv4, IPv6, IGMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS                                                                             |
| Compatible Integration           | API, SDK, ONVIF (Profile S, Profile G, Profile T, Profile M)                                                                                                                                               |
| User/Host                        | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                     |
| Security                         | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                           | EZStation, APP                                                                                                                                                                                             |

|                     |                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Web Browser         | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                                                                                    |
| Interface           |                                                                                                                                                                                                                                                                     |
| Audio I/O           | N/A                                                                                                                                                                                                                                                                 |
| Alarm I/O           | N/A                                                                                                                                                                                                                                                                 |
| Serial Port         | N/A                                                                                                                                                                                                                                                                 |
| Built-in Mic        | Support                                                                                                                                                                                                                                                             |
| Built-in Speaker    | N/A                                                                                                                                                                                                                                                                 |
| WIFI                | N/A                                                                                                                                                                                                                                                                 |
| Network             | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                                                                                |
| Video Output        | N/A                                                                                                                                                                                                                                                                 |
| Certification       |                                                                                                                                                                                                                                                                     |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)<br>FCC (FCC 47 CFR part15 B)                                                                                                                                                                            |
| Safety              | CE LVD (EN 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                                                                                                                                                                                               |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                                                                                                                                                                                               |
| Protection          | IP67 (IEC 60529)<br>IK10 (IEC 62262)                                                                                                                                                                                                                                |
| General             |                                                                                                                                                                                                                                                                     |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                                                                                                                                     |
| Power Consumption   | Max. 5.5 W                                                                                                                                                                                                                                                          |
| Power Interface     | Ø5.5 mm coaxial power plug                                                                                                                                                                                                                                          |
| Dimensions          | Ø111 mm × 93 mm (Ø4.4" × 3.7") (Ø × H)                                                                                                                                                                                                                              |
| Weight              | 0.48 kg (1.06 lb.)                                                                                                                                                                                                                                                  |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Surge Protection    | 4 KV                                                                                                                                                                                                                                                                |
| Reset Button        | Support                                                                                                                                                                                                                                                             |
| Material            | Metal                                                                                                                                                                                                                                                               |
| Web Client Language | 20 Languages: Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese |

## Dimensions



## Accessories

|                                                                                     |                                                                                     |                                                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>TR-JB03-G-IN</b><br>Junction Box for Mini Fix-dome(Support wiring from behind)   | <b>TR-A01-IN</b><br>NPT 3/4" Waterproof Cable Gland                                 | <b>TR-SE24-IN</b><br>Dome Pendent Mounting Pole 200mm                                                               |
|  |  |                                |
| <b>TR-SE24-A-IN</b><br>Dome Pendent Mounting Pole 500mm                             | <b>TR-CM24-IN</b><br>Dome Pendent Mounting Bracket(Indoor)                          | <b>TR-JB07/WM03-G-IN-V2</b><br>Wall Mounting Assembling Bracket For 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera |
|  |  |                                |

| <b>TR-WM03-D-IN-V2</b><br>Wall Mounting Bracket for 32<br>Fix-dome&Mini Fix-dome&Plastic Turret<br>Camera | <b>TR-UC08-C-V2</b><br>Bullet&Dome Corner Mounting Bracket                        | <b>TR-UP06-C-IN-V2</b><br>Pole Mounting Bracket for Bullet Junction<br>Box Only     |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                          |  |  |

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.