UISP Network

Datasheet
UISP-S-Pro

UISP Switch Pro



UI.COM

Mechanical

Dimensions	442.4 x 267.5 x 43.7 mm (17.4 x 10.5 x 1.7")
Weight	4 kg (8.8 lb)
Enclosure materials	SGCC steel, polycarbonate/acrylonitrile butadiene styrene

Hardware

Total non-blocking throughput	64 Gbps
Switching capacity	128 Gbps
Forwarding rate	95.23 Mpps
Networking interface	(24) GbE RJ45 LAN ports (4) 1/10G SFP+ ports
Management interface	Ethernet In-Band Bluetooth
Power method	(1) Universal AC input, 100—240V AC, 4.4A Max., 50/60 Hz (1) Power TransPort DC input 27V DC, 9.3A
Power supply	AC/DC, Internal, 250W
Supported voltage range	100—240V AC
Max. power consumption	30W (ExcludING PoE output)
ESD/EMP protection	Air: ± 15 kV, contact: ± 8 kV
LCM display	(1) 1.3" touchscreen
Operating temperature	-10 to 50° C (14 to 122° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

PoE

PoE interface	(16) 27V passive PoE: 2-pair (Pins 4, 5+/7, 8-) or 4-pair (Pins 1, 2, 4, 5+/3, 6, 7, 8-); Ports 1 to 16
Total available PoE	220W
Max. passive PoE wattage per port	30W/27V DC
Passive PoE voltage range	27V DC

LEDs

RJ45 data ports	PoE Speed/link/activity
SFP+ data ports	Speed/link/activity

Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: ui.com/support/warranty

©2022 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, and UISP are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.